

## TECHNICAL SPECIFICATIONS

# GSA3(M,Q)E Series

### High Efficiency Air Conditioner 14.3 SEER2 Manufactured Housing System 2 – 4 Ton Capacity

The GSA3(M,Q)E Series of air conditioners offer exceptional performance. The unit, when combined with our engineered coils or air handlers, offers a full line of quality, split system cooling equipment.




## FEATURES and BENEFITS

- **Designed for Manufactured Housing:** Charged with refrigerant for 20 feet of lineset.
- **Full Service Valves on GSA3ME:** These brass valves are easily accessible and simplify servicing of the refrigeration system.
- **Quick Connect Fittings on GSA3QE:** No brazing or evacuation required, reducing install time.
- **Designed Using Galvanized Steel:** A powder-coated paint that eliminates sharp edges and reduces corrosion, fading, chipping and scratching. It passes 950 hours of salt spray per ASTM Std. B117.
- **Composite Base Pan:** Absorbs sound and is corrosion resistant. Composite is also stronger and lighter than steel.
- **Permanently Lubricated Motor:** A heavy duty PSC motor for long lasting reliability and quiet operation. Requires no maintenance and is completely protected from rain and snow.
- **Removable Top Grille Assembly:** Allows ease of service from the top without disconnecting fan motor leads.
- **High Pressure Switch:** Protects against abnormally high system pressures. Auto-reset feature prevents nuisance service visits.
- **Liquid Line Filter Drier:** Included with unit, factory installed on QE and field installed on ME models.
- **One Piece Top/Orifice:** Designed for maximum airflow and quiet operation.
- **Easy Compressor and Control Access:** Designed to make servicing easier for the contractor, access panels are provided to all controls and the compressor from the side of the unit.
- **All-Aluminum coils:** Aluminum coils in all models which provides high corrosion resistance.
- **Powder Coated Wire Guard and Mesh Hail Guard:** Will never rust and protects the coil from being damaged by balls, lawnmowers, hail, etc.




## MODEL IDENTIFICATION CODES



## DIMENSIONS

### AIR CONDITIONER OUTDOOR SECTION

| GSA3(M,Q)E | 24K   | 30K   | 36K   | 42K   | 48K   |
|------------|-------|-------|-------|-------|-------|
| H          | 27.0  | 31.0  | 31.0  | 39.0  | 39.0  |
| W          | 30.75 | 30.75 | 30.75 | 30.75 | 30.75 |
| D          | 30.75 | 30.75 | 30.75 | 30.75 | 30.75 |



# PHYSICAL AND ELECTRICAL SPECIFICATIONS / OUTDOOR UNITS

## 14.3 SEER2 — High Efficiency — Single Phase

| Model Number GSA3(M,Q)E4M1                                                         |                        | RN24K        | RN30K | SN36K | SN42K    | SN48K |
|------------------------------------------------------------------------------------|------------------------|--------------|-------|-------|----------|-------|
| Electrical Data                                                                    | Volts-Cycles-Phase (1) | 208/230-60-1 |       |       |          |       |
|                                                                                    | Delay Fuse Max. (2)    | 20           | 25    | 30    | 40       | 45    |
|                                                                                    | Min. Circuit Ampacity  | 12.4         | 15.7  | 17.2  | 23.5     | 26.2  |
|                                                                                    | Locked Rotor Amp       | 43.0         | 52.0  | 83.1  | 110.2    | 110.0 |
|                                                                                    | Fan Motor              | HP           | 1/8   | 1/8   | 1/8      | 1/4   |
| Refrigerant suction line O.D.<br>NOTE: Liquid line is 3/8" O.D. for entire length. |                        | 0-24 ft.     | 3/4"  | 3/4"  | 3/4"     | 7/8"  |
|                                                                                    |                        | 25-39 ft.    | 3/4"  | 3/4"  | 7/8" (3) | 7/8"  |
|                                                                                    |                        | 40-75 ft.    | 3/4"  | 3/4"  | 7/8" (3) | 7/8"  |
| Approximate Shipping Weight (lbs.)                                                 |                        | GSA3ME       | 152   | 161   | 167      | 205   |
|                                                                                    |                        | GSA3QE       | 151   | 160   | 167      | 205   |
| Sound Rating (dBA)                                                                 |                        | 75           | 75    | 75    | 79       | 79    |

(1) Operating Voltage Range: 187v min. - 253v max.

(2) HACR Type Circuit Breakers may be used.

(3) Requires 7/8" to 3/4" reducer from line to unit.

## ACCESSORIES - Condensing Unit

### Start Assist Kit - 912933

Provides additional starting torque for the compressor motor when operating with low line voltage or high operating temperatures.

### Low Ambient Kit - 918837

## SYSTEM COOLING CAPACITIES

### 14.3 SEER2 — High Efficiency — Single Phase

| Manufactured Housing Gas Furnace |              |        |       |      |       |          |
|----------------------------------|--------------|--------|-------|------|-------|----------|
| Outdoor Unit                     | Indoor Unit  | BTUH   | SEER2 | EER2 | CFM   | AHRI DTC |
| GSA3ME4M1RN24K                   | C84DAMX24U-B | 23,400 | 14.3  | 11.7 | 800   | YES      |
| GSA3ME4M1RN30K                   | C84DAMX30U-B | 28,400 | 14.3  | 11.7 | 1,005 | YES      |
| GSA3ME4M1SN36K                   | C84DAMX36U-B | 35,000 | 14.3  | 11.7 | 1,180 | YES      |
| GSA3ME4M1SN42K                   | C84DAMX42U-B | 39,500 | 14.3  | 11.7 | 1,230 | YES      |
| GSA3ME4M1SN48K                   | C84DAMX48U-B | 45,000 | 13.8  | 11.2 | 1,410 | YES      |
|                                  |              |        |       |      |       |          |
| GSA3QE4M1RN24K                   | C84QAMX24U-B | 23,400 | 14.3  | 11.7 | 800   | YES      |
| GSA3QE4M1RN30K                   | C84QAMX30U-B | 28,400 | 14.3  | 11.7 | 1,005 | YES      |
| GSA3QE4M1SN36K                   | C84QAMX36U-B | 35,000 | 14.3  | 11.7 | 1,180 | YES      |
| GSA3QE4M1SN42K                   | C84QAMX42U-B | 39,500 | 14.3  | 11.7 | 1,230 | YES      |
| GSA3QE4M1SN48K                   | C84QAMX48U-B | 45,000 | 13.8  | 11.2 | 1,410 | YES      |

See current AHRI Directory for certified combinations and ratings. All ratings are with time delay relay.  
[www.ahridirectory.org](http://www.ahridirectory.org)

# COOLING EXPANDED RATINGS WITH COIL

GSA3(M,Q)E4M1RN24K + C84(D,Q)AMX24U-B

| O.D.T |        |        | 65°F |      |      | 75°F |      |      | 85°F |      |      | 95°F |      |      | 105°F |      |      | 115°F |      |      |
|-------|--------|--------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|------|-------|------|------|
| CFM   | E.D.B. | E.W.B. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C.  | S.C. | K.W. | T.C.  | S.C. | K.W. |
| 700   | 80     | 62     | 24.8 | 21.1 | 1.38 | 23.9 | 20.6 | 1.52 | 22.8 | 20.0 | 1.69 | 21.5 | 19.3 | 1.88 | 20.1  | 19.0 | 2.08 | 18.5  | 18.1 | 2.28 |
|       | 80     | 67     | 27.1 | 17.8 | 1.35 | 26.1 | 17.4 | 1.50 | 24.9 | 16.8 | 1.68 | 23.5 | 16.3 | 1.88 | 22.0  | 15.5 | 2.09 | 20.3  | 14.9 | 2.30 |
|       | 80     | 72     | 29.4 | 14.5 | 1.31 | 28.4 | 14.1 | 1.47 | 27.1 | 13.6 | 1.67 | 25.6 | 13.0 | 1.87 | 23.9  | 12.3 | 2.09 | 22.1  | 11.6 | 2.31 |
|       | 75     | 62     | 24.7 | 17.9 | 1.38 | 23.9 | 17.5 | 1.52 | 22.8 | 17.0 | 1.69 | 21.4 | 16.3 | 1.88 | 20.0  | 15.6 | 2.08 | 18.5  | 14.9 | 2.28 |
|       | 75     | 67     | 26.9 | 14.6 | 1.35 | 26.0 | 14.2 | 1.50 | 24.8 | 13.7 | 1.68 | 23.4 | 13.1 | 1.88 | 21.9  | 12.4 | 2.09 | 20.2  | 11.7 | 2.29 |
| 800   | 80     | 62     | 25.4 | 22.3 | 1.41 | 24.4 | 21.8 | 1.56 | 23.3 | 21.4 | 1.73 | 21.9 | 20.9 | 1.92 | 20.5  | 20.0 | 2.12 | 19.0  | 19.0 | 2.33 |
|       | 80     | 67     | 27.7 | 18.8 | 1.38 | 26.6 | 18.3 | 1.53 | 25.4 | 17.8 | 1.72 | 24.0 | 17.2 | 1.92 | 22.3  | 16.6 | 2.13 | 20.5  | 15.6 | 2.34 |
|       | 80     | 72     | 30.1 | 15.1 | 1.33 | 29.0 | 14.7 | 1.50 | 27.8 | 14.2 | 1.70 | 26.1 | 13.5 | 1.91 | 24.3  | 12.8 | 2.13 | 22.4  | 12.1 | 2.35 |
|       | 75     | 62     | 25.3 | 18.8 | 1.41 | 24.4 | 18.5 | 1.56 | 23.2 | 17.8 | 1.73 | 21.8 | 17.2 | 1.92 | 20.3  | 16.6 | 2.12 | 18.7  | 16.0 | 2.32 |
|       | 75     | 67     | 27.5 | 15.2 | 1.38 | 26.6 | 14.8 | 1.54 | 25.3 | 14.3 | 1.72 | 23.9 | 13.7 | 1.92 | 22.2  | 13.0 | 2.13 | 20.5  | 12.2 | 2.34 |
| 900   | 80     | 62     | 25.8 | 23.9 | 1.45 | 24.8 | 23.4 | 1.59 | 23.6 | 22.8 | 1.77 | 22.2 | 21.9 | 1.96 | 20.9  | 20.9 | 2.17 | 19.5  | 19.5 | 2.37 |
|       | 80     | 67     | 28.1 | 19.7 | 1.41 | 27.1 | 19.2 | 1.57 | 25.8 | 18.7 | 1.76 | 24.2 | 18.0 | 1.96 | 22.6  | 17.2 | 2.17 | 20.7  | 16.7 | 2.38 |
|       | 80     | 72     | 30.5 | 15.6 | 1.36 | 29.4 | 15.2 | 1.54 | 28.0 | 14.6 | 1.74 | 26.4 | 14.0 | 1.95 | 24.5  | 13.3 | 2.17 | 22.6  | 12.6 | 2.39 |
|       | 75     | 62     | 25.7 | 19.7 | 1.45 | 24.8 | 19.3 | 1.59 | 23.5 | 18.7 | 1.77 | 22.1 | 18.3 | 1.96 | 20.6  | 17.6 | 2.16 | 18.9  | 16.8 | 2.37 |
|       | 75     | 67     | 28.0 | 15.8 | 1.41 | 27.0 | 15.3 | 1.57 | 25.7 | 14.8 | 1.76 | 24.1 | 14.2 | 1.96 | 22.5  | 13.5 | 2.17 | 20.7  | 12.7 | 2.38 |

GSA3(M,Q)E4M1RN30K + C84(D,Q)AMX30U-B

| O.D.T |        |        | 65°F |      |      | 75°F |      |      | 85°F |      |      | 95°F |      |      | 105°F |      |      | 115°F |      |      |
|-------|--------|--------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|------|-------|------|------|
| CFM   | E.D.B. | E.W.B. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C.  | S.C. | K.W. | T.C.  | S.C. | K.W. |
| 875   | 80     | 62     | 30.5 | 26.1 | 1.68 | 29.3 | 25.5 | 1.89 | 27.7 | 24.3 | 2.08 | 25.8 | 23.9 | 2.28 | 23.8  | 22.9 | 2.50 | 21.9  | 21.8 | 2.74 |
|       | 80     | 67     | 33.5 | 21.8 | 1.65 | 32.1 | 21.3 | 1.87 | 30.3 | 20.5 | 2.07 | 28.3 | 19.7 | 2.28 | 26.2  | 18.8 | 2.51 | 24.0  | 17.8 | 2.77 |
|       | 80     | 72     | 36.4 | 17.7 | 1.62 | 34.9 | 17.1 | 1.84 | 33.0 | 16.4 | 2.05 | 30.8 | 15.5 | 2.28 | 28.5  | 14.6 | 2.52 | 26.2  | 13.7 | 2.78 |
|       | 75     | 62     | 30.4 | 22.0 | 1.68 | 29.2 | 21.4 | 1.89 | 27.6 | 20.7 | 2.08 | 25.8 | 19.8 | 2.28 | 23.8  | 18.9 | 2.50 | 21.9  | 18.0 | 2.74 |
|       | 75     | 67     | 33.3 | 17.9 | 1.66 | 32.0 | 17.4 | 1.87 | 30.2 | 16.5 | 2.07 | 28.2 | 15.6 | 2.28 | 26.1  | 14.7 | 2.51 | 24.0  | 13.8 | 2.76 |
| 1005  | 80     | 62     | 31.3 | 27.8 | 1.73 | 29.9 | 27.1 | 1.93 | 28.2 | 26.5 | 2.13 | 26.3 | 25.5 | 2.33 | 24.3  | 24.3 | 2.55 | 22.6  | 22.6 | 2.81 |
|       | 80     | 67     | 34.2 | 23.1 | 1.70 | 32.8 | 22.6 | 1.92 | 30.9 | 21.8 | 2.12 | 28.8 | 20.9 | 2.33 | 26.5  | 19.9 | 2.57 | 24.3  | 19.0 | 2.82 |
|       | 80     | 72     | 37.2 | 18.5 | 1.67 | 35.6 | 17.8 | 1.89 | 33.6 | 17.0 | 2.10 | 31.3 | 16.1 | 2.33 | 28.9  | 15.2 | 2.57 | 26.5  | 14.3 | 2.84 |
|       | 75     | 62     | 31.2 | 23.3 | 1.73 | 29.8 | 22.6 | 1.93 | 28.2 | 21.9 | 2.13 | 26.2 | 21.0 | 2.33 | 24.2  | 20.1 | 2.55 | 22.1  | 19.1 | 2.80 |
|       | 75     | 67     | 34.1 | 18.6 | 1.70 | 32.7 | 18.1 | 1.92 | 30.8 | 17.2 | 2.12 | 28.7 | 16.4 | 2.33 | 26.5  | 15.3 | 2.56 | 24.3  | 14.4 | 2.82 |
| 1125  | 80     | 62     | 31.8 | 28.8 | 1.77 | 30.4 | 28.8 | 1.98 | 28.6 | 27.8 | 2.18 | 26.7 | 26.7 | 2.38 | 25.0  | 25.0 | 2.61 | 23.2  | 23.2 | 2.86 |
|       | 80     | 67     | 34.8 | 24.2 | 1.74 | 33.3 | 23.7 | 1.96 | 31.3 | 22.8 | 2.17 | 29.0 | 21.7 | 2.38 | 26.8  | 21.0 | 2.62 | 24.5  | 19.7 | 2.88 |
|       | 80     | 72     | 37.8 | 19.1 | 1.71 | 36.1 | 18.4 | 1.93 | 34.0 | 17.6 | 2.15 | 31.7 | 16.7 | 2.37 | 29.2  | 15.8 | 2.62 | 26.7  | 14.8 | 2.89 |
|       | 75     | 62     | 31.7 | 24.4 | 1.77 | 30.3 | 23.8 | 1.98 | 28.6 | 23.0 | 2.18 | 26.5 | 22.1 | 2.38 | 24.4  | 20.9 | 2.60 | 22.3  | 20.1 | 2.85 |
|       | 75     | 67     | 34.7 | 19.3 | 1.74 | 33.1 | 18.7 | 1.96 | 31.2 | 17.9 | 2.17 | 28.8 | 16.6 | 2.38 | 26.8  | 15.9 | 2.62 | 24.5  | 15.0 | 2.87 |

GSA3(M,Q)E4M1SN36K + C84(D,Q)AMX36U-B

| O.D.T |        |        | 65°F |      |      | 75°F |      |      | 85°F |      |      | 95°F |      |      | 105°F |      |      | 115°F |      |      |
|-------|--------|--------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|------|-------|------|------|
| CFM   | E.D.B. | E.W.B. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C.  | S.C. | K.W. | T.C.  | S.C. | K.W. |
| 1050  | 80     | 62     | 38.6 | 32.3 | 2.14 | 36.6 | 31.6 | 2.35 | 34.6 | 30.1 | 2.58 | 32.6 | 29.6 | 2.84 | 30.3  | 28.6 | 3.12 | 27.5  | 27.0 | 3.43 |
|       | 80     | 67     | 41.8 | 27.1 | 2.15 | 39.8 | 26.3 | 2.36 | 37.9 | 25.3 | 2.59 | 35.8 | 24.5 | 2.85 | 33.4  | 23.3 | 3.13 | 30.6  | 22.2 | 3.43 |
|       | 80     | 72     | 44.8 | 21.9 | 2.17 | 42.7 | 20.9 | 2.37 | 40.7 | 20.1 | 2.59 | 38.7 | 19.4 | 2.85 | 36.2  | 18.4 | 3.13 | 33.0  | 17.1 | 3.42 |
|       | 75     | 62     | 38.5 | 27.6 | 2.14 | 36.5 | 26.6 | 2.35 | 34.6 | 25.7 | 2.58 | 32.5 | 24.7 | 2.83 | 30.4  | 23.5 | 3.12 | 27.6  | 21.9 | 3.42 |
|       | 75     | 67     | 41.6 | 22.3 | 2.16 | 39.7 | 21.5 | 2.36 | 37.7 | 20.6 | 2.59 | 35.7 | 19.7 | 2.85 | 33.4  | 18.6 | 3.13 | 30.4  | 17.4 | 3.43 |
| 1195  | 80     | 62     | 39.5 | 34.3 | 2.21 | 37.3 | 32.8 | 2.41 | 35.3 | 32.5 | 2.64 | 33.2 | 31.6 | 2.90 | 30.8  | 30.3 | 3.19 | 28.3  | 28.3 | 3.50 |
|       | 80     | 67     | 42.7 | 28.4 | 2.22 | 40.6 | 27.6 | 2.43 | 38.5 | 26.8 | 2.66 | 36.3 | 25.9 | 2.91 | 33.9  | 24.7 | 3.19 | 30.9  | 23.2 | 3.49 |
|       | 80     | 72     | 45.7 | 22.6 | 2.24 | 43.5 | 21.8 | 2.44 | 41.4 | 21.0 | 2.66 | 39.3 | 20.1 | 2.91 | 36.8  | 19.1 | 3.18 | 33.4  | 17.8 | 3.47 |
|       | 75     | 62     | 39.3 | 29.0 | 2.21 | 37.2 | 28.0 | 2.41 | 35.2 | 27.1 | 2.64 | 33.1 | 26.1 | 2.90 | 30.9  | 24.9 | 3.18 | 28.0  | 23.1 | 3.48 |
|       | 75     | 67     | 42.6 | 23.2 | 2.23 | 40.5 | 22.2 | 2.43 | 38.4 | 21.3 | 2.66 | 36.3 | 20.5 | 2.91 | 33.9  | 19.4 | 3.19 | 30.9  | 18.1 | 3.49 |
| 1350  | 80     | 62     | 40.2 | 36.3 | 2.28 | 37.9 | 35.6 | 2.48 | 35.8 | 34.6 | 2.71 | 33.6 | 33.1 | 2.97 | 31.6  | 31.6 | 3.25 | 29.1  | 29.1 | 3.56 |
|       | 80     | 67     | 43.4 | 29.8 | 2.29 | 41.3 | 29.0 | 2.50 | 39.1 | 28.1 | 2.72 | 36.8 | 27.2 | 2.98 | 34.3  | 25.9 | 3.26 | 31.2  | 24.5 | 3.55 |
|       | 80     | 72     | 46.4 | 23.5 | 2.31 | 44.1 | 22.6 | 2.51 | 42.0 | 21.7 | 2.72 | 39.8 | 20.8 | 2.97 | 37.2  | 19.8 | 3.25 | 33.7  | 18.5 | 3.54 |
|       | 75     | 62     | 40.0 | 30.5 | 2.28 | 37.8 | 29.5 | 2.48 | 35.7 | 28.6 | 2.71 | 33.5 | 27.6 | 2.96 | 31.2  | 26.3 | 3.25 | 28.3  | 24.4 | 3.55 |
|       | 75     | 67     | 43.2 | 24.0 | 2.30 | 41.1 | 23.1 | 2.50 | 39.0 | 22.1 | 2.72 | 36.7 | 21.2 | 2.97 | 34.4  | 20.1 | 3.25 | 31.2  | 18.6 | 3.55 |

# COOLING EXPANDED RATINGS WITH COIL

GSA3(M,Q)E4M1SN42K + C84(D,Q)AMX42U-B

| O.D.T |        |        | 65°F |      |      | 75°F |      |      | 85°F |      |      | 95°F |      |      | 105°F |      |      | 115°F |      |      |
|-------|--------|--------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|------|-------|------|------|
| CFM   | E.D.B. | E.W.B. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C.  | S.C. | K.W. | T.C.  | S.C. | K.W. |
| 1230  | 80     | 62     | 42.1 | 36.3 | 2.41 | 40.1 | 35.5 | 2.61 | 38.2 | 34.3 | 2.85 | 36.3 | 33.7 | 3.11 | 34.1  | 32.8 | 3.41 | 31.6  | 31.1 | 3.72 |
|       | 80     | 67     | 45.8 | 30.3 | 2.40 | 43.7 | 29.3 | 2.61 | 41.9 | 28.6 | 2.85 | 39.8 | 27.8 | 3.13 | 37.6  | 26.9 | 3.42 | 34.7  | 25.3 | 3.74 |
|       | 80     | 72     | 49.1 | 24.2 | 2.39 | 46.9 | 23.3 | 2.61 | 45.2 | 22.7 | 2.85 | 43.3 | 21.9 | 3.12 | 40.9  | 21.0 | 3.42 | 37.7  | 19.7 | 3.74 |
|       | 75     | 62     | 42.0 | 30.7 | 2.41 | 40.0 | 29.8 | 2.61 | 38.1 | 28.9 | 2.85 | 36.3 | 28.0 | 3.11 | 34.2  | 26.9 | 3.40 | 31.6  | 25.4 | 3.71 |
| 1400  | 75     | 67     | 45.6 | 24.8 | 2.40 | 43.6 | 23.9 | 2.61 | 41.7 | 23.0 | 2.85 | 39.7 | 22.1 | 3.12 | 37.5  | 21.2 | 3.42 | 34.7  | 20.0 | 3.73 |
|       | 80     | 62     | 43.0 | 38.6 | 2.48 | 40.9 | 37.3 | 2.68 | 38.8 | 36.9 | 2.92 | 36.9 | 35.9 | 3.19 | 34.7  | 34.4 | 3.48 | 32.5  | 32.5 | 3.80 |
|       | 80     | 67     | 46.7 | 31.9 | 2.47 | 44.6 | 30.8 | 2.68 | 42.6 | 30.4 | 2.93 | 40.5 | 29.5 | 3.20 | 38.1  | 28.4 | 3.50 | 35.2  | 26.7 | 3.81 |
|       | 80     | 72     | 50.0 | 25.2 | 2.46 | 48.0 | 24.4 | 2.68 | 45.9 | 23.5 | 2.92 | 43.9 | 22.7 | 3.20 | 41.5  | 21.7 | 3.50 | 38.2  | 20.5 | 3.81 |
| 1575  | 75     | 62     | 42.8 | 32.4 | 2.48 | 40.7 | 31.4 | 2.68 | 38.8 | 30.5 | 2.92 | 36.8 | 29.6 | 3.18 | 34.7  | 28.6 | 3.48 | 32.0  | 26.8 | 3.79 |
|       | 75     | 67     | 46.5 | 25.7 | 2.47 | 44.3 | 24.8 | 2.69 | 42.4 | 24.0 | 2.93 | 40.3 | 23.0 | 3.20 | 38.0  | 22.1 | 3.49 | 35.1  | 20.7 | 3.80 |
|       | 80     | 62     | 43.7 | 40.5 | 2.55 | 41.5 | 40.0 | 2.75 | 39.4 | 38.8 | 2.99 | 37.6 | 37.6 | 3.26 | 35.7  | 35.7 | 3.56 | 33.3  | 33.3 | 3.87 |
|       | 80     | 67     | 47.4 | 33.2 | 2.55 | 45.2 | 32.3 | 2.76 | 43.2 | 31.8 | 3.00 | 40.9 | 30.9 | 3.27 | 38.6  | 29.9 | 3.57 | 35.5  | 28.5 | 3.88 |
| 1575  | 80     | 72     | 50.7 | 26.0 | 2.54 | 48.7 | 25.2 | 2.75 | 46.7 | 24.4 | 3.00 | 44.5 | 23.6 | 3.27 | 41.9  | 22.6 | 3.57 | 38.5  | 21.3 | 3.88 |
|       | 75     | 62     | 43.5 | 34.0 | 2.55 | 41.3 | 33.1 | 2.75 | 39.3 | 32.2 | 2.99 | 37.3 | 31.2 | 3.26 | 35.1  | 30.0 | 3.55 | 32.3  | 28.4 | 3.86 |
|       | 75     | 67     | 47.2 | 26.7 | 2.55 | 45.1 | 25.8 | 2.76 | 43.0 | 24.8 | 3.00 | 40.9 | 23.8 | 3.27 | 38.4  | 22.8 | 3.57 | 35.4  | 21.5 | 3.88 |

GSA3(M,Q)E4M1SN48K + C84(D,Q)AMX48U-B

| O.D.T |        |        | 65°F |      |      | 75°F |      |      | 85°F |      |      | 95°F |      |      | 105°F |      |      | 115°F |      |      |
|-------|--------|--------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|------|-------|------|------|
| CFM   | E.D.B. | E.W.B. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C. | S.C. | K.W. | T.C.  | S.C. | K.W. | T.C.  | S.C. | K.W. |
| 1490  | 80     | 62     | 48.4 | 42.4 | 2.89 | 46.3 | 41.5 | 3.11 | 44.3 | 40.4 | 3.39 | 42.1 | 39.7 | 3.72 | 39.8  | 38.5 | 4.09 | 36.9  | 36.7 | 4.48 |
|       | 80     | 67     | 52.6 | 35.6 | 2.89 | 50.3 | 34.5 | 3.12 | 48.2 | 33.5 | 3.41 | 46.0 | 32.6 | 3.75 | 43.4  | 31.5 | 4.13 | 40.3  | 30.1 | 4.51 |
|       | 80     | 72     | 56.4 | 28.4 | 2.88 | 54.1 | 27.5 | 3.12 | 52.1 | 26.8 | 3.42 | 49.7 | 25.8 | 3.76 | 47.0  | 24.7 | 4.14 | 43.5  | 23.4 | 4.54 |
|       | 75     | 62     | 48.3 | 35.8 | 2.89 | 46.1 | 34.7 | 3.11 | 44.1 | 33.7 | 3.39 | 42.0 | 32.6 | 3.72 | 39.6  | 31.5 | 4.09 | 36.7  | 30.1 | 4.48 |
| 1600  | 75     | 67     | 52.5 | 29.0 | 2.88 | 50.2 | 28.0 | 3.12 | 48.1 | 27.1 | 3.41 | 45.9 | 26.2 | 3.75 | 43.3  | 25.2 | 4.13 | 40.1  | 23.8 | 4.51 |
|       | 80     | 62     | 49.0 | 44.0 | 2.94 | 46.8 | 42.8 | 3.16 | 44.6 | 42.0 | 3.44 | 42.5 | 41.0 | 3.77 | 40.1  | 39.5 | 4.14 | 37.5  | 37.5 | 4.53 |
|       | 80     | 67     | 53.2 | 36.6 | 2.93 | 50.8 | 35.5 | 3.17 | 48.6 | 34.5 | 3.46 | 46.4 | 33.7 | 3.80 | 43.8  | 32.3 | 4.18 | 40.5  | 31.0 | 4.56 |
|       | 80     | 72     | 56.9 | 29.1 | 2.93 | 54.6 | 28.2 | 3.17 | 52.5 | 27.3 | 3.47 | 50.2 | 26.4 | 3.81 | 47.4  | 25.4 | 4.19 | 43.8  | 24.1 | 4.59 |
| 1800  | 75     | 62     | 48.8 | 36.7 | 2.94 | 46.6 | 35.9 | 3.16 | 44.5 | 34.8 | 3.44 | 42.3 | 33.6 | 3.77 | 39.9  | 32.7 | 4.14 | 36.9  | 31.4 | 4.52 |
|       | 75     | 67     | 53.0 | 29.6 | 2.93 | 50.7 | 28.7 | 3.17 | 48.5 | 27.8 | 3.46 | 46.3 | 26.9 | 3.80 | 43.6  | 25.7 | 4.17 | 40.3  | 24.3 | 4.56 |
|       | 80     | 62     | 49.7 | 46.6 | 3.02 | 47.5 | 45.6 | 3.24 | 45.2 | 44.4 | 3.52 | 43.1 | 42.9 | 3.86 | 41.0  | 41.0 | 4.23 | 38.4  | 38.4 | 4.62 |
|       | 80     | 67     | 53.9 | 38.2 | 3.01 | 51.5 | 37.2 | 3.25 | 49.3 | 36.2 | 3.54 | 46.9 | 35.2 | 3.89 | 44.2  | 34.5 | 4.26 | 40.8  | 33.2 | 4.65 |
| 1800  | 80     | 72     | 57.7 | 30.1 | 3.01 | 55.3 | 29.1 | 3.26 | 53.1 | 28.3 | 3.55 | 50.7 | 27.4 | 3.90 | 47.9  | 26.3 | 4.28 | 44.1  | 24.9 | 4.67 |
|       | 75     | 62     | 49.6 | 38.4 | 3.02 | 47.3 | 37.4 | 3.24 | 45.1 | 36.9 | 3.52 | 42.8 | 35.8 | 3.86 | 40.3  | 34.7 | 4.23 | 37.2  | 33.2 | 4.61 |
| 1800  | 75     | 67     | 53.7 | 30.7 | 3.01 | 51.3 | 29.8 | 3.25 | 49.1 | 28.8 | 3.54 | 46.8 | 27.8 | 3.88 | 44.1  | 26.6 | 4.26 | 40.7  | 25.2 | 4.65 |



#### GENERAL TERMS OF LIMITED WARRANTY

Nortek Global HVAC, LLC will furnish a replacement for any part of this product which fails in normal use and service within the terms and conditions of the warranty.

For complete details of the Limited Warranty, including applicable terms and conditions, see your local installer or contact the Nortek Global HVAC, LLC warranty department for a copy.

Before purchasing this appliance, read important energy cost and efficiency information available from your retailer. Specifications and illustrations subject to change without notice and without incurring obligations. Printed in U.S.A (06/2022)